



*	Hriadelova Zátka/ Shaft Plug	Zátka/ Plug	Note/ Poznamka
A	So zátkou/ With plug	So zátkou/ With plug	Standard
B	So zátkou/ With plug	Bez zátky/ Without plug	Na požiadanie/ On request
C	Bez zátky/ Without plug	So zátkou/ With plug	Na požiadanie/ On request
D	Bez zátky/ Without plug	Bez zátky/ Without plug	Na požiadanie/ On request

#	i	Poznamka/ Note
A	43	Standard
C	73	Standard
D	95	Standard

Vers/Revs	Change	Date	Signature
Material	-		
Semi-Product	-		
Attachment		Techn.Prepared	
Design Prepared	Jackovic	27-Aug-20	Techn.Checked
Design Checked	Klucar		Confirmed
Manuf.Checked		Valid From	
TS 095-i-G-P14-0820*			TS 095G
Description		Type	

SPINEA
EXCELLENCE IN MOTION

Undimensioned Edges = 0.3x45°
Untoleranced Dimensions - STN ISO 2768-mK

Weight [kg] **2.197** Scale **1:1**
Position -

Model Name/ Vers. 095_000G_P14_0820_P/
Drawing Name/Vers. 095_000G_P14_0820_P/

Sheet/Sheets 1/1 ARTIKEL -

0-820 P*0 #00-3 -/-

Drawing-No Vers/Revs

Note:
- Main ring must be fixed in operation with
18pcs of SCREW M4 St 12.9, TIGHTENING TORQUE 5Nm