













*	Hriadelova Zatka/ Shaft Plug	Zatka/ Plug	Note/ Poznamka
A	**So zatkou/ With plug**	**So zatkou/ With plug**	**Standard**
B	**So zatkou/ With plug**	Bez zatky/ Without plug	Na poziadanie/ On request
C	Bez zatky/ Without plug	**So zatkou/ With plug**	Na poziadanie/ On request
D	Bez zatky/ Without plug	Bez zatky/ Without plug	Na poziadanie/ On request

#	i	Poznamka/ Note
B	57	Standard
C	67	Standard
F	117	Standard
L	139	Standard

Note:
- Main ring must be fixed in operation with 30pcs of SCREW M6 St 12.9 TIGHTENING TORQUE 17Nm

Vers/Revs	Change	Date	Signature

Material	-				
Semi-Product	- -			Pieces	-
Attachment			Techn.Prepared		
Design Prepared	Jackovic	22-Mar-19	Techn.Checked		
Design Checked	R.KLUCAR		Confirmed	-	
Manuf.Checked		Valid From			
TS 185-i-G-P24-0801*				TS 185G	
Description				Type	

SPINEA
EXCELLENCE IN MOTION

	Undimensioned Edges = 0.3x45°		
	Untoleranced Dimensions - STN ISO 2768-mK		
Weight [kg]	14.539	Scale	1:1.7
		Position	1
Model Name/ Vers.	185_000G_P24_0801_P/ -.5		
Drawing Name/Vers.	185_000G_P24_0801_P/		
Sheet/Sheets	1/1	ARTIKEL	390182-
0-801 P*0 #00-3			-/-
Drawing-No			Vers/Revs

For this drawing we reserve all rights. Without our permission it may neither be copied nor made accessible to third persons. All patent trademark and other right in this drawing and are expressly reserved by SPINEA Ltd.

-A3-