



Note:

- MAIN RING MUST BE IN OPERATION FIXED
- 18pcs SCREW M2,5 St 12.9
- TORQUE 1,1Nm

*	Hriadelova Zátka/ Shaft Plug	Zátka/ Plug	Note/ Poznamka
A	So zátkou/ With plug	So zátkou/ With plug	Standard
B	So zátkou/ With plug	Bez zátky/ Without plug	Na požiadanie/ On request
C	Bez zátky/ Without plug	So zátkou/ With plug	Na požiadanie/ On request
D	Bez zátky/ Without plug	Bez zátky/ Without plug	Na požiadanie/ On request

Vers/Revs	Change	Date	Signature
Material	-		
Semi-Product	-		Pieces -
Attachment		Techn.Prepared	
Design Prepared	Cesar 20-Oct-16	Techn.Checked	
Design Checked	Klucar	Confirmed	
Manuf.Checked		Valid From	B.Janek
TS 75-i-G-P9-0438*		75G	
Description		Type	

SPINEA
EXCELLENCE IN MOTION

Undimensioned Edges = 0.3x45°
Intoleranced Dimensions - STN ISO 2768-mK

Weight [kg] **0.946** Scale **1:1**
Position -

Model Name/ Vers. 075_000G_P9_0438_P/ B.2
Drawing Name/Vers. 075_000G_P9_0438_P/ A.2

Sheet/Sheets 1/1 ARTIKEL **390752-D003**

0-438 P*0 #00-3 -/-

Drawing-No Vers/Revs