





B
2:1



Note:
- MAIN RING MUST BE IN OPERATION FIXED
  18pcs SCREW M4 St 12.9
  TORQUE 5Nm
- Unsealed space, see assembly manual in catalogue TS
- RECOMENDATION: Sealing diameter on the sealing flange (Ø71 -0,03 -0,06)

*	Hriadelova Zatka/ Shaft Plug	Zatka/ Plug	Note/ Poznamka
A	**So zatkou/ With plug**	**So zatkou/ With plug**	**Standard**
B	**So zatkou/ With plug**	Bez zatky/ Without plug	Na poziadanie/ On request
C	Bez zatky/ Without plug	**So zatkou/ With plug**	Na poziadanie/ On request
D	Bez zatky/ Without plug	Bez zatky/ Without plug	Na poziadanie/ On request

Vers/Revs	Change	Date	Signature

Material	-				
Semi-Product	- -			Pieces	-
Attachment			Techn.Prepared		
Design Prepared	Ceslar	14-Aug-19	Techn.Checked		
Design Checked	Klucar		Confirmed	-	
Manuf.Checked		Valid From			
TS 95-i-G-P14-0683				95 G	
Description				Type	

SPINEA
EXCELLENCE IN MOTION

	Undimensioned Edges = 0,3x45°		
	Untoleranced Dimensions - STN ISO 2768-mK		
Weight [kg]	1.924	Scale	1:1
		Position	-
Model Name/ Vers.	095_000G_P14_0683P/		
Drawing Name/Vers.	095_000G_P14_0683P/		
Sheet/Sheets	1/1	ARTIKEL	390952-#00#
0-683 P*0 #00-3			-/-
Drawing-No			Vers/Revs

For this drawing we reserve all rights. Without our permission it may neither be copied nor made accessible to third persons. All patent trademark and other right in this drawing and are expressly reserved by SPINEA Ltd.

-A3-